

Multi-Application (MA) Series

5.25" or 6.5" 70/25V Commercial Speaker System



SP6MAT Shown

Speco Technologies' **Multi-Application (MA) Series** was designed to make the contractor's work as easy and time-efficient as possible.

Our all-in-one unit, pre-assembled with a back can and mounted transformer, features a quick flip 70 or 25 Volt selector switch and an easy select transformer wattage dial featuring the choice of 8 or 9 individual wattage tap settings covering your complete range of needs.

This fire-retardant, ABS unit also comes with insulated wires and has an attached metal safety loop and easy mount tabs for securing the unit.

Specifications

| | SP5MAT 5.25" 70/25V Commercial Speaker System | SP6MAT 6.5" 70/25V Commercial Speaker System |
|-----------------------------|--|---|
| Woofer | 5.25" Polypropylene with Rubber Surround | 6.5" Polypropylene with Rubber Surround |
| Tweeter | 1" Mylar Tweeter | 1" Mylar Tweeter |
| Frequency | 57Hz –20kHz | 34Hz –20kHz |
| Power | 30 Watt RMS/ 60 Watt Max | 40 Watt RMS/ 80 Watt Max |
| Sensitivity | 87 db 1w/1m | 88 db 1w/1m |
| Impedance | 8 ohms | 8 ohms |
| Weight | 4.5 lbs. | 5.5 lbs |
| Transformer | 70/25 Volt | 70/25 Volt |
| Transformer Settings | 30, 15, 7.5, 5, 2.5, 1, .50, .25, 8ohm | 40, 30, 15, 7.5, 5, 2.5, 1, .50, .25, 8ohm |
| In-Ceiling Bracket Supports | BRC6F | BRC8F |
| Dimensions | 9.5" Dia. x 6" Depth | 11" Dia. x 7.5" Depth |
| Mounting Dimensions | 8 3/8" Diameter | 9 7/8" Diameter |



Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
 Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880